

## Tullbefrielser som upphör den 31/12-2020 till följd av för låg importvolym - reviderad lista

### Ansökan om ny förlängning kan göras för dessa varor

TARIC codes	Description
1513193020	#Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:### # industrial monocarboxylic fatty acids of subheading 3823 19 10, # methyl esters of fatty acids of heading 2915 or 2916, # fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, # fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, # stearic acid of subheading 3823 11 00, # goods of heading 3401, or # fatty acids with high purity of heading 2915 #
1512191010	#Refined safflower oil (CAS RN 8001-23-8) for use in the manufacture of### # conjugated linoleic acid of heading 3823 or # ethyl- or methyl esters of linoleic acid of heading 2916 #
2008994894	#Mango puree:### # not from concentrate, # of the genus Mangifera, # of a Brix value of 14 or more, but not more than 20 # ###used in the manufacture of products of drink industry#
2008999940	#Seedless boysenberry puree not containing added spirit, whether or not containing added sugar#
2009419220	#Pineapple juice:### # not from concentrate, # of the genus Ananas , # of a Brix value of 11 or more but not more than 16, # ###used in the manufacture of products of drink industry#
2811220015	#Amorphous silicon dioxide (CAS RN 60676-86-0),### # in the form of powder # of a purity by weight of 99,0 % or more # with a median grain size of 0,7 µm or more, but not more than 2,1 µm # where 70 % of the particles have a diameter of not more than 3 µm #
2903740010	#2-Chloro-1,1-difluoroethane (CAS RN 338-65-8)#
2904200020	Nitroethane (CAS RN 79-24-3)
2905490010	#Ethylidynetrimethanol (CAS RN 77-85-0)#
2906290040	#2-Bromo-5-iodo-benzenemethanol (CAS RN 946525-30-0)#
2909500020	#Ubiquinol (CAS RN 992-78-9)#
2911000010	#Ethoxy-2,2-difluoroethanol (CAS RN 148992-43-2)#
2914500065	#3-Methoxyacetophenone (CAS RN 586-37-8)#
2914500075	#7-Hydroxy-3,4-dihydro-1(2H)-naphthalenone (CAS RN 22009-38-7)#
2914790015	#1-(4-Methylphenyl)-4,4,4-trifluorobutane-1,3-dione (CAS RN 720-94-5)#
2914790025	#1-(7-Bromo-9,9-difluoro-9H-fluoren-2-yl)-2-chloroethanone (CAS RN 1378387-81-5)#
2916399051	#3-Chloro-2-fluorobenzoic acid (CAS RN 161957-55-7)#

2916399061	#2-Phenylbutyric Acid (CAS RN 90-27-7)#
2920290030	#2,2'-[[3,3',5,5'-Tetrakis(1,1-dimethylethyl)[1,1'-biphenyl]-2,2'-diyl]bis(oxy)]bis[biphenyl-1,3,2-dioxaphosphepine], (CAS RN 138776-88-2)#
2921420033	#2-Fluoroaniline (CAS RN 348-54-9)#
2921430050	#4-Aminobenzotrifluoride (CAS RN 455-14-1)#
2921490080	#4-Heptafluoroisopropyl-2-methylaniline (CAS RN 238098-26-5)#
2921511970	#4-Bromo- 1,2-diaminobenzene (CAS RN 1575-37-7)#
2921599070	#Tris(4-aminophenyl)methane (CAS RN 548-61-8)#
2922290040	#4-Hydroxy-6-[(3-sulphophenyl)amino]naphthalene-2-sulphonic acid (CAS RN 25251-42-7)#
2922390025	#3-(Dimethylamino)-1-(1-naphthalenyl)-1-propanone)hydrochloride (CAS RN 5409-58-5)#
2924190020	#(R)-(-)-3-(carbamoylmethyl)-5-methylhexanoic acid (CAS RN 181289-33-8)#
2924297060	#N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 41131-65-1)#
2924297061	#( S )-1-Phenylethanamine ( S )-2-(((1 R ,2 R )-2-allylcyclopropoxy)carbonylamino)-3,3-dimethylbutanoate (CUS 0143288-8)#
2925290030	#Guanidine sulphamate (CAS RN 50979-18-5)#
2926907014	#Cyanoacetic acid (CAS RN 372-09-8)#
2930909810	#2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)#
2930909819	#N-(2-Methylsulfinyl-1,1-dimethyl-ethyl)-N'-(2-methyl-4-[1,2,2,2-tetrafluoro-1-(trifluoromethyl)ethyl]phenyl}phthalamide (CAS RN 371771-07-2)#
2930909857	#Methyl (methylthio)acetate (CAS RN 16630-66-3)#
2931399057	#Trimethyl phosphonoacetate (CAS RN 5927-18-4)#
2931900005	#Diethylmethoxyborane (CAS RN 7397-46-8), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN#
2931900067	#Dimethyltin dioleate (CAS RN 3865-34-7)#
2931900070	#(4-Propylphenyl)boronic acid (CAS RN 134150-01-9)#
2932190020	#Tetrahydrofuran-borane (CAS RN 14044-65-6)#
2933199035	#1,3-Dimethyl-5-fluoro-1H-pyrazole-4-carbonyl fluoride (CAS RN 191614-02-5)#
2933299065	#(S)-tert-Butyl 2-(5-bromo-1H-imidazol-2-yl)pyrrolidine-1-carboxylate (CAS RN 1007882-59-8)#
2933399913	#Methyl (1S,3S,4R)-2-[(1R)-1-phenylethyl]-2-azabicyclo[2.2.1]hept-5-ene-3-carboxylate (CAS RN 130194-96-6)#
2933399914	#N,4-Dimethyl-1-(phenylmethyl)- 3-piperidinamine hydrochloride (1:2) (CAS RN 1228879-37-5)#
2933399916	#Methyl (2S,5R)-5-[(benzyloxy)amino]piperidine-2-carboxylate dihydrochloride (CAS RN 1501976-34-6)#
2933399917	#3,5-Dimethylpyridine (CAS RN 591-22-0)#
2933399919	#Methyl nicotinate (INNM) (CAS RN 93-60-7)#
2933399923	#2-Chloro-3-cyanopyridine (CAS RN 6602-54-6)#
2933399926	#2-[4-(Hydrazinylmethyl)phenyl]-pyridine dihydrochloride (CAS RN 1802485-62-6)#
2933499040	#Isoquinoline (CAS RN 119-65-3)#

2933499080	#Ethyl 6,7,8-trifluoro-1-[formyl(methyl)amino]-4-oxo-1,4-dihydroquinoline-3-carboxylate (CAS RN 100276-65-1)#
2933599518	#1-Methyl-3-phenylpiperazine (CAS RN 5271-27-2)#
2933599553	#5-Fluoro-2-methoxypyrimidin-4(3H)-one (CAS RN 1480-96-2)#
2933998017	#Carfentrazone-ethyl (ISO) (CAS RN 128639-02-1) with a purity by weight of 93 % or more#
2933998026	##(2 S , 3 S , 4 R )-Methyl 4-(3-(1,1-difluorobut-3-enyl)-7-methoxyquinoxalin-2-yloxy)-3-ethylpyrrolidine-2-carboxylate 4-methylbenzenesulfonate (CUS 0143289-9)#
2933998029	#3-[3-(4-Fluorophenyl)-1-(1-methylethyl)-1H-indol-2-yl]-(E)-2-propenal (CAS RN 93957-50-7)#
2933998052	#N-Boc-trans-4-Hydroxy-L-proline methyl ester (CAS RN 74844-91-0) #
2934208060	#Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)#
2934999031	#Uridine 5'-diphospho-N-acetylgalactosamine disodium salt (CAS RN 91183-98-1)#
2934999032	#Uridine 5'-diphosphoglucuronic acid trisodium salt (CAS RN 63700-19-6)#
2934999034	#7-[4-(Diethylamino)-2-ethoxyphenyl]-7-(1-ethyl-2-methyl-1H-indol-3-yl)furo[3,4-b]pyridin-5(7H)-one (CAS RN 69898-40-4)#
2934999050	#10-[1,1'-Biphenyl]-4-yl-2-(1-methylethyl)-9-oxo-9 H -thioxanthenium hexafluorophosphate, (CAS RN 591773-92-1)#
2935909052	##(1 R , 2 R )-1-Amino-2-(difluoromethyl)-N-(1-methylcyclopropylsulphonyl) cyclopropanecarboxamide hydrochloride (CUS 0143290-2)#
2935909058	#1-Methylcyclopropane-1-sulphonamide (CAS RN 669008-26-8)#
3204170016	#Colourant C.I. Pigment Red 49:2 (CAS RN 1103-39-5) and preparations based thereon with a colourant C.I. Pigment Red 49:2 content of 60 % or more by weight#
3204190071	#Colourant C.I. Solvent Brown 53 (CAS RN 64696-98-6) and preparations based thereon with a colourant C.I. Solvent Brown 53 content of 95 % or more by weight#
3208101010	#Thermoplastic polyester copolymer resin with a solid content of 30 % or more but not more than 50 %, in organic solvents##### #
3402901030	#Surface-active preparation, consisting of a mixture of sodium docusate and ethoxylated 2,4,7,9-tetramethyldec-5-yne-4,7-diol (CAS RN 577-11-7 and 9014-85-1)#
3402901050	#Surface-active preparation, consisting of a mixture of polysiloxane and poly(ethylene glycol)#
3402901060	#Surface-active preparation, containing 2-ethylhexyloxymethyl oxirane#
3507909020	#Creatine amidinohydrolase (CAS RN 37340-58-2)##### #
3808939030	#Aqueous solution containing by weight:### # 1,8 % of sodium para-nitrophenolate, # 1,2 % of sodium ortho-nitrophenolate, # 0,6 % of sodium 5-nitroguaiacolate # ###for use in the manufacture of a plant growth regulator #
3808939040	#Mixed white powder containing by weight:### # 3 % or more but not more than 3,6 % of 1-methylcyclopropene with a purity more than 96 % and # containing less than 0,05 % of each impurity of 1-chloro-2-methylpropene and 3-chloro-2-methylpropene # ###for use in the manufacture of a growth regulator of post-harvest fruits, vegetables and ornamentals with a specific generator#
3808999010	#Oxamyl (ISO) (CAS RN 23135-22-0) in a solution of cyclohexanone and water#
3811210075	#Additives containing:### # Calcium (C10-C14) dialkylbenzenesulfonates, # more than 40 %, but not more than 60 % by weight of mineral oils, # ###with a total base number of not more than 10, for use in the manufacture of blends of additives for lubricating oils#

3811210077	#Antifoam additives consisting of:### # a copolymer of 2-ethylhexyl acrylate and ethyl acrylate, and # more than 50 % but not more than 80 % by weight of mineral oils # ###for use in the manufacture of additive blends for lubricating oils#
3811210080	#Additives containing :### # polyisobutylene aromatic polyamine succinimide, # more than 40 % but not more than 60 % by weight of mineral oils, # ###with a nitrogen content of more than 0,6 % but not more than 0,9 % by weight, for use in the manufacture of additive blends for lubricating oils#
3811290065	#Additives consisting of a sulphurised mixture of vegetable oil, long chain $\alpha$ -olefins and tall oil fatty acids, with a sulphur content of 8 % or more but not more than 12 % by weight, for use in the manufacture of blends of additives for lubricating oils#
3824999228	#Aqueous solution containing by weight### # 10 % or more but not more than 42 % of 2-(3-chloro-5-(trifluoromethyl)pyridin-2-yl)ethanamine (CAS RN 658066-44-5), # 10 % or more but not more than 25 % of sulphuric acid (CAS RN 7664-93-9) and # 0,5 % or more but not more than 2,9 % of methanol (CAS RN 67-56-1) #
3824999246	#Diethylmethoxyborane (CAS RN 7397-46-8) in the form of a solution in tetrahydrofuran#
3824999260	#N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride in a solution of dichloromethane at 37 %#
3901400020	#Octene linear low-density polyethylene (LLDPE) in the form of pellets of a kind used in the co-extrusion processing of films for flexible food packaging with:### # 10 % or more but not more than 20 % by weight of octene, # a melt flow ratio of 9,0 or more, but not more than 10,0 (using ASTM D1238 10.0/2.16), # a melt index (190°C/2.16 kg) of 0,4 g / 10 min or more but not more than 0,6 g / 10 min, # a density of 0,909 g/cm <sup>3</sup> or more, but not more than 0,913 g/cm <sup>3</sup> using ASTM D4703, # a gel area per 24,6 cm <sup>3</sup> of not more than 20 mm <sup>2</sup> ; and # an anti-oxidant level of not more than 240 ppm #
3901400040	#Block copolymer of ethylene with octene in the form of pellets:### # with a specific gravity of 0,862 or more, but not more than 0,865, # able to stretch to at least 200 % its original length, # with a hysteresis of 50 % ( $\pm 10$ %), # with permanent deformation of not more than 20 %, # ###for use in the manufacture of napkin liners for babies #
3901908070	#Ethylene maleic anhydride copolymer, whether or not containing another olefin comonomer, with a melt flow rate of 1,3g/10 min or more at 190 °C/2,16 kg (measured using ASTM D1238)#
3903909046	#Copolymer in the form of granules containing by weight:### # 74 % ( $\pm 4$ %) styrene, # 24 % ( $\pm 2$ %) n-butylacrylate and # 0,01 % or more but not more than 2 % methacrylic acid #
3906909040	#Transparent acrylic polymer in packages of not more than 1 kg, and not for retail sale with:### # a viscosity of not more than 50000 Pa·s at 120 °C as determined by the test method ASTM D 3835 # a weight average molecular weight (M <sub>w</sub> ) of more than 500 000 but not more than 1 200 000 according to the Gel Permeation Chromatography (GPC) test, # a residual monomer content of less than 1 % #
3907100010	#Mixture of a trioxan-oxirane-copolymer and polytetrafluoroethylene#
3907100020	#Polyoxymethylene with acetyl endcaps, containing polydimethylsiloxane and fibers of a copolymer of terephthalic acid and 1,4-phenyldiamine#
3908900055	#1,4-Benzenedicarboxylic acid polymer with 2-methyl-1,8-octanediamine and 1,9-nonanediamine (CAS RN 169284-22-4)#
3910000015	#Dimethyl, methyl(propyl(polypropylene oxide)) siloxane (CAS RN 68957-00-6), trimethylsiloxy-terminated#

3911909930	#1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated#
3919108043,	#Ethylene vinyl acetate film:### # of a thickness of 100 µm or more, # coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester or polypropylene liner #
3919908052	#White polyolefin tape consisting of:### # an adhesive layer based on synthetic rubber with a thickness of 8 µm or more but not more than 17 µm, # a polyolefin layer with a thickness of 28 µm or more but not more than 40 µm, and # a non-silicone release layer with a thickness below 1 µm #
3919908063	#Co-extruded trilayer film,### # each layer containing a mixture of polypropylene and polyethylene, # containing not more than 3 % by weight of other polymers, # whether or not containing titanium dioxide in the core layer, # coated with an acrylic pressure sensitive adhesive and # with a release liner # of an overall thickness of not more than 110 µm #
3921905550	#Glass fibre-reinforced sheets of reactive, halogen-free epoxide resin with hardener, additives and inorganic fillers for use in encapsulating semiconductor systems#
5402470020	#Bicomponent monofilament yarn of not more than 30 dtex, consisting of:### # a poly(ethylene terephthalate) core, and # an outer layer of a copolymer of poly(ethyleneterephthalate) and poly(ethyleneisophthalate), # ###for use in the manufacture of filtration fabrics#
5403390010	#Biodegradable (norm EN 14995) monofilament of not more than 33 dtex, containing at least 98 % by weight polylactide (PLA), for use in the manufacture of filtration fabrics for the food industry#
7004908010	#Alkali-aluminosilicate drawn flat glass sheet with:### # a scratch proof coating of a thickness of 45 µm (+/- 5 µm), # a total thickness of 0,45 mm or more but not more than 1,1 mm, # a width of 300 mm or more but not more than 3210 mm, # a length of 300 mm or more but not more than 2 000 mm, # a visible light transmission of 90 % or more; # an optical distortion of 55° or more #
7009910010	#Unframed glass mirrors with:### # a length of 1516 mm (± 1 mm); # a width of 553 mm (± 1 mm); # a thickness of 3 mm (± 0,1 mm); # the back of the mirror covered with protective polyethylene (PE) film, with a thickness of 0,11 mm or more but not more than 0,13 mm; # a lead content of not more than 90 mg/kg and # a corrosion resistance of 72 hours or more according to ISO 9227 salt spray test #
7604291010, 7606129920	#Sheets and bars of aluminium-lithium alloys#
8108200040	#Titanium alloy ingot,## with a height of 17,8 cm or more, a length of 180 cm or more and a width of 48,3cm or more, a weight of 680 kg or more, #containing alloy elements by weight of:## 3 % or more but not more than 6 % of aluminium, 2,5 % or more but not more than 5 % of tin, 2,5 % or more but not more than 4,5 % of zirconium, 0,2 % or more but not more than 1 % of niobium, 0,1 % or more but not more than 1 % of molybdenum, 0,1 % or more but not more than 0,5 % of silicon
8302200020	#Castors, with### # an external diameter of 21 mm or more but not more than 23 mm, # a width with screw of 19 mm or more but not more than 23 mm, # a U-shaped plastic outer ring, # an assembly screw fitted to the internal diameter and used as an inner ring #
8413703520	#Single phase centrifugal pump:### # discharging at least 400 cm <sup>3</sup> fluid per minute, # with a noise level limited to 6 dBA, # with the inside diameter of the suction opening and discharge outlet of not more than 15 mm, and # working at ambient temperatures down to -10°C #
8414592540	#Axial fan with an electric motor, of an output of not more than 2 W, for use in the manufacture of products of heading 8521 or 8528 #

8415900030	#Aluminium arc-welded removable receiver dryer with a connection block, containing polyamide and ceramic elements, with:### # a length of 166 mm (+/- 1 mm), # a diameter of 70 mm (+/- 1 mm), # an internal capacity of 280 cm <sup>3</sup> or more, # a water absorption rate of 17 g or more, and # an internal purity expressed by permissible amount of impurities of not more than 0,9 mg/dm <sup>2</sup> # ###of a kind used in car air-conditioning
8415900055	#Aluminium arc-welded removable receiver dryer with polyamide and ceramic elements with:### # a length of 143 mm or more but not more than 292 mm, # a diameter of 31 mm or more but not more than 99 mm, # a spangle length of not more than 0,2 mm and a thickness of not more than 0,06 mm, and # a solid particle diameter of not more than 0,06 mm # ###of a kind used in car air-conditioning systems#
8479899785	#High Pressure Hard Materials Compression Press ("Link Press"):### # with a 16 000 tonne pressure rating, # with a 1 100mm diameter Bolster (± 1mm), # with a 1 400mm main cylinder (± 1mm), # with a Fixed and floating link frame, multiple pump high pressure hydraulic accumulator and pressure system, # with a double arm manipulator arrangement and connections for piping and electrical systems, # with a total weight 310 tonnes (± 10 tonnes), and # creating 30 000 atmospheres at 1 500 degrees centigrade using Low Frequency Alternating Current (16 000 amps) #
8501101020	#Synchronous motor for a dishwasher with a water flow control mechanism with### # a length without axle of 24 mm (+/- 0,3), # a diameter of 49,3 mm (+/- 0,3) # a rated voltage of 220 V AC or more but not more than 240 V AC, # a rated frequency of 50 Hz or more but not more than 60 Hz, # an input power of not more than 4 W, # a rotation speed of 4rpm or more but not more than 4,8rpm, # an output torque of not less than 10kgf/cm #
8501612035	#Fuel cell module , AC generator with an output of 7.5 kVA or less, consisting of:### # a Hydrogen generator (desulphurizer, reformer and cleaner ) # a PEM fuel cell stack and # an Inverter # ###for use as a part in a heating appliance#
8505199040	#Flat bars of an alloy of samarium and cobalt with### # a length of 30,4 mm (± 0,05 mm); # a width of 12,5 mm (± 0,15 mm); # a thickness of 6,9 mm (± 0,05 mm), or composed of ferrites in the shape of a quarter sleeves with: # a length of 46 mm (± 0,75 mm); # a width of 29,7 mm (± 0,2 mm), # ###intended to become permanent magnets after magnetisation, of a kind used in car starters and devices extending the drive range of electric cars#
8508700010, 8537109896	#Printed circuit board without a housing for actuating and controlling vacuum cleaner brushes powered by a motor with an output of not more than 300 W#
8512309020	#Warning buzzer for parking sensor system in a plastic casing operating on the piezo-mechanic principle, containing:### # a printed circuit board, # a connector, # whether or not a metal holder # ###of a kind used in the manufacture of goods of chapter 87#
8525801965	#Cameras using MIPI electrical interface with:### # an image sensor, # an objective (lens), # a colour processor, # a flexible printed circuit board or a printed circuit board, # whether or not capable of receiving audio signals, # a module dimension of not more than 15mm x 15mm x 15mm , # a resolution of 2 mega pixel or more (1616*1232 pixels and higher), # whether or not wired, and # a housing # ###for use in the manufacture of products falling within subheading 8517 12 00 or 8471 30 00#
8535900030	#Semiconductor module switch in a casing:### # consisting of an IGBT transistor chip and a diode chip on one or more lead frames, # for a voltage of 600 V or 1 200 V #
8536699060	#Electrical sockets and plugs with a length of not more than 12,7 mm or a diameter of not more than 10,8 mm, for use in the production of hearing aids and speech processors#

8537109835	#Electronic control unit without memory, for a voltage of 12 V, for information exchange systems in vehicles (for connection of audio, telephony, navigation, camera and wireless car service) containing:### # 2 rotary knobs # 27 or more pushbuttons # LED lights # 2 integrated circuits for receiving and sending of control signals via the LIN-bus #
8543709095	#Mobile telephone view and control module comprising of:### # a mains power/ CAN (Controller area network) output socket, # a universal serial bus (USB) and audio IN/OUT ports and # incorporating a video switching device for the interface of smart phone operating systems with the Media Orientated Systems Transport network (MOST), # ###for use in the manufacture of vehicles of Chapter 87#
8545909020	#Carbon fibre paper of a kind used for gas diffusion layers in fuel cell electrodes#
8708301070	#Ductile cast iron brake caliper jaw, of a kind used in the manufacture of goods of Chapter 87#
8708502020	#Transmission shaft in carbon fibre reinforced plastics consisting of a unique piece without any joint in the middle### # of a length of 1 m or more but not more than 2 m, # of a weight of 6 kg or more but not more than 9 kg #
8708802010	#Upper strut insulator containing### # a metal holder with three mounting screws, and # a rubber bump # ###of a kind used in the manufacture of goods of Chapter 87#
8708802020	#Rear chassis arm with a protective plastic label equipped with two metal casings with pressed-in rubber silent blocks, of kind used in the manufacture of goods of Chapter 87#
8708802030	#Rear chassis arm equipped with a ball pivot and metal casing with a pressed-in rubber silent block, of kind used in the manufacture of goods of Chapter 87#
8708912030	#Aluminium alloy inlet or outlet air tank manufactured to standard EN AC 42100 with:### # an insulating area flatness of not more than 0,1 mm, # a permissible particle quantity of 0,3 mg per tank, # a distance between pores of 2 mm or more, # pore sizes of not more than 0,4 mm, and # not more than 3 pores larger than 0,2mm # ###of a kind used in heat exchangers for car cooling systems#
8708951010	#Inflatable safety cushion of high strength polyamide fibre### # sewn # folded into three-dimensional packing form, fixed by thermal forming #
8708951020	#Inflatable safety cushion of high strength polyamide fibre:### # sewn, # folded, # with three-dimensionally applied silicone bonding for air bag cavity forming and load-regulated air bag sealing # suitable for cool inflator technology #
8714109020	#Radiators of a kind used in motor bikes for fitting of attachments#
9002110015	#Infrared lens with motorised focus adjustment,### # using wavelengths of 3 µm or more but not more than 5 µm, # providing a clear picture from 50 m to infinity, # with fields of vision sizes of 3° x 2,25° and 9° x 6,75 °, # with a weight of not more than 230 g, # with a length of not more than 88 mm, # with a diameter of not more than 46 mm, # athermalized, # ###for use in the manufacture of thermal imaging cameras, infrared binoculars, weapons scopes#
9401908060	#Outer part of a headrest made of perforated bovine leather, lined with a scrim-reinforced lamination liner and without foam padding, after reworking (stitching of the leather and embroidery application) used in manufacture of seats of motor vehicles#
9503007510	#Plastic cable car scale models, whether or not with a motor, for printing#
9607201010	#Sliders, narrow tape with mounted zipper teeth, pin/boxes and other parts of slide fasteners, of base metal for use in the manufacture of zippers#