

TARIC code(s)	Product description
2009899996	#Coconut water#### # unfermented, # not containing added spirit or sugar, and # in immediate packing of a content of 20 litres or more #
2825700020	#Molybdic Acid (CAS RN 7782-91-4)#
2845909030	#( 13 C)Carbon monoxide (CAS RN 1641-69-6)#
2903190020	#1,3-Dichloropropane (CAS RN 142-28-9) with a purity by weight of 99 % or more#### #
2903691940	#3-(Bromomethyl)pentane (CAS RN 3814-34-4) with a purity by weight of 99 % or more#
2903691960	#1-Bromo-2-methylpropane (CAS RN 78-77-3) with a purity by weight of 99 % or more#
2904990065	#4-Nitrotoluene-2-sulphonic acid (CAS RN 121-03-9) in powder form, with a purity by weight of 80 % or more and a content of water by weight of 15 % or more#
2908190070	#2,3,6-Trifluorophenol (CAS RN 113798-74-6) with a purity by weight of 98 % or more#
2909309015	#[(2,2-Dimethylbut-3-yn-1-yl)oxy]methyl}benzene (CAS RN 1092536-54-3)#
2909309045	#5-Bromo-1,3-difluoro-2-(trifluoromethoxy)benzene (CAS RN 115467-07-7) with a purity by weight of 95 % or more#
2914409010	#Benzoin (CAS RN 119-53-9) with a purity by weight of 99 % or more#
2914500023	#1-[2-(Oxiran-2-ylmethoxy)phenyl]-3-phenylpropan-1-one (CAS RN 22525-95-7) with a purity by weight of 99 % or more#
2916399025	#2-Methyl-3-(4-Fluorophenyl)-propionyl chloride (CAS RN 1017183-70-8)#
2916399063	#2-Phenylbutyric acid (CAS RN 90-27-7) with a purity by weight of 99 % or more#
2916399073	#(2,4-Dichlorophenyl)acetyl chloride (CAS RN 53056-20-5)#
2918300055	#Methyl 3-oxo-pentanoate (CAS RN 30414-53-0) with a purity by weight of 98 % or more#
2918999048	#2-Bromo-5-methoxybenzoic acid (CAS RN 22921-68-2) with a purity by weight of 98 % or more#
2921199945	#2-Chloro- N -(2-chloroethyl)ethanamine hydrochloride (CAS RN 821-48-7)#
2921290035	#Pentamethylenediamine (CAS RN 462-94-2) with a purity by weight of 99 % or more, also as an aqueous solution containing by weight more than 50 % of pentamethylenediamine#
2922190040	#(R)-1-((4-Amino-2-bromo-5-fluorophenyl)amino)-3-(benzyloxy)propan-2-ol 4-methylbenzenesulphonate (CAS RN 1294504-64-5)#
2922498523	#2-Ethylhexyl 4-aminobenzoate (CAS RN 26218-04-2) with a purity by weight of 99 % or more#
2922498533	#4-Amino-2-chlorobenzoic acid (CAS RN 2457-76-3) with a purity by weight of 98 % or more#
2923900030	#Tetrabutylammonium tetrahydroborate (CAS RN 33725-74-5) with a purity by weight of 97 % or more#
2924190038	#Diethyl acetamidomalonate (CAS RN 1068-90-2) with a purity by weight of 98 % or more#
2924190048	# N,N -Dimethylcarbamoyl chloride (CAS RN 79-44-7) with a purity by weight of 99 % or more#
2924297032	# N -(4-Amino-2-ethoxyphenyl)acetamide (CAS RN 848655-78-7) with a purity by weight of 98 % or more#

2924297035	#N-(1,1-Dimethylethyl)-4-amino-benzamide (CAS RN 93483-71-7) with a purity by weight of 99 % or more#
2924297036	# N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 41131-65-1) with a purity by weight of 97 % or more#
2924297052	#Zoxamide (ISO) (CAS RN 156052-68-5) with a purity by weight of 97 % or more#
2926907056	#Methyl 2-cyano-2-propylpentanoate (CAS RN 66546-92-7) with a purity by weight of 97 % or more#
2928009030	# N -Isopropylhydroxylamine (CAS RN 5080-22-8)#
2930909532	#2-Methoxy-N-[2-nitro-5-(phenylsulfanyl)phenyl]acetamide (CAS RN 63470-85-9) with a purity by weight of 96 % or more#
2930909578	#4-Mercaptomethyl-3,6-dithia-1,8-octanedithiol (CAS RN 131538-00-6)#
2932209060	#6'-(Diethylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3 H ),9'-[9 H ]xanthen]-3-one (CAS RN 29512-49-0)#
2932990013	#(4-Chloro-3-(4-ethoxybenzyl)phenyl)((3aS,5R,6S,6aS)-6-hydroxy 2,2-dimethyltetrahydrofuro[2,3-d][1,3]dioxol-5-yl)methanone (CAS RN 1103738-30-2)#
2932990018	#4-(4-Bromo-3-((tetrahydro-2H-pyran-2-yloxy)methyl)phenoxy)benzotrile (CAS RN 943311-78-2)#
2932990028	#1,4,7,10,13-Pentaoxacyclopentadecane (CAS RN 33100-27-5) with a purity by weight of 90 % or more, the remainder mainly consisting of linear precursors#
2933199045	#5-Amino-1-[2,6-dichloro-4-(trifluoromethyl)phenyl]-1H-pyrazole-3-carbonitrile (CAS RN 120068-79-3)#
2933210050	#1-Bromo-3-chloro-5,5-dimethylhydantoin (CAS RN 16079-88-2) / (CAS RN 32718-18-6)#
2933299020	#tert-Butyl (2S)-2-(5-bromo-1H-imidazol-2-yl)pyrrolidine-1-carboxylate (CAS RN 1007882-59-8) with a purity by weight of 98 % or more#
2933299060	#1-Cyano-2-methyl-1-[2-(5-methylimidazol-4-ylmethylthio)ethyl]isothiourea (CAS RN 52378-40-2)#
2933399910	#2-Aminopyridin-4-ol hydrochloride (CAS RN 1187932-09-7)#
2933399932	#2-(Chloromethyl)-3,4-dimethoxypyridine hydrochloride (CAS RN 72830-09-2)#
2933399942	#Glasdegib maleate (INN) (CAS RN 2030410-25-2) with a purity by weight of 98 % or more#
2933599529	#2-Amino-4-(4-methylpiperazin-1-yl) benzoic acid tert-butyl ester (CAS RN 1034975-35-3) with a purity by weight of 95 % or more#
2933599538	#5-(5-Chlorosulfonyl-2-ethoxyphenyl)-1-methyl-3-propyl-1,6-dihydro-7H-pyrazolo[4,3-d]pyrimidin-7-one (CAS RN 139756-22-2) with a purity by weight of 98 % or more#
2933599541	#2-(4-Phenoxyphenyl)-7-(piperidin-4-yl)-4,5,6,7-tetrahydropyrazolo[1,5-a]pyrimidine-3-carbonitrile (CAS RN 2190506-57-9) with a purity by weight of 98 % or more#
2933599587	#5-Bromo-2,4-dichloropyrimidine (CAS RN 36082-50-5)#
2933790055	#(3S,4R)-3-Amino-4-hydroxypyrrolidin-2-one hydrochloride (CAS RN 2446872-13-3) with a purity by weight of 98 % or more#### #
2933998009	#5,7-Difluoro-2-(4-fluorophenyl)-1H-indole (CAS RN 901188-04-3) with a purity by weight of 98 % or more#
2933998022	#Dibenz[b,f]azepine-5-carbonyl chloride (CAS RN 33948-22-0) with a purity by weight of 98 % or more#

2933998038	#(4a S ,7a S )-Octahydro-1 H -pyrrolo[3,4-b]pyridine (CAS RN 151213-40-0)#
2933998042	#(S)-2,2,4-Trimethylpyrrolidine hydrochloride (CAS RN 1897428-40-8)#
2933998067	#Candesartan ethyl ester (INNM) (CAS RN 139481-58-6)#
2933998080	#Pyrrole-2-carboxaldehyde (CAS RN 1003-29-8) with a purity by weight of 97 % or more#
2934999035	#Nusinersen sodium (INNM) (CAS RN 1258984-36-9) with a purity by weight of 95 % or more#
2934999040	#2,3-Pyrazinedicarboxylic anhydride (CAS RN 4744-50-7) with a purity by weight of 95 % or more#
2934999065	#Benzo[b]thiophen-10-methoxycycloheptanone (CAS RN 59743-84-9) with a purity by weight of 98 % or more#
2934999085	#Gilteritinib (INN) (CAS 1254053-43-4) with a purity by weight of 98 % or more and its salts#
2935909018	#4-Amino-2,5-dimethoxy-N-methylbenzenesulfonamide (CAS RN 49701-24-8) with a purity by weight of 98 % or more#
2935909019	#4-Amino-2,5-dimethoxy-N-phenylbenzenesulphonamide (CAS RN 52298-44-9) with a purity by weight of 98 % or more#
2935909021	#Encorafenib (INN) (CAS 1269440-17-6) with a purity by weight of 99 % or more#
2935909027	#Methyl (3R,5S,6E)-7-{4-(4-fluorophenyl)-6-isopropyl-2-[methyl(methylsulfonyl)amino]pyrimidin-5-yl}-3,5-dihydroxyhept-6-enoate (CAS RN 147118-40-9) #
2935909030	#6-Aminopyridine-2-sulfonamide (CAS RN 75903-58-1)#
3204120055	#Colourant C.I. Acid Brown 165 (CAS RN 61724-14-9) and preparations based thereon with a colourant C.I. Acid Brown 165 content of 75 % or more by weight#
3811210012	#Dispersing agent containing :### # esters of polyisobutenyl succinic acid and pentaerythritol (CAS RN 103650-95-9), # 35 % or more but not more than 55 % by weight of mineral oils, and # with a chlorine content of not more than 0,05 % by weight, # ###used in the manufacture of blends of additives for lubricating oils#
3811210022	#Additive consisting essentially of:### # Polyisobutenyl succinic anhydride (CAS RN 192662-34-3) reaction product with N,N-diethylaminoethanol (CAS RN 100-37-8), # 25 % or more by weight, but not more than 40 % by weight of mineral oil, # ###used in the manufacture of blends of additives for lubricating oils#
3811210024	#Additive consisting essentially of:### # Polyisobutenyl succinic anhydride reaction product with polyethylenepolyamines, borated (CAS RN 134758-95-5), with a chlorine content by weight of 0,05 % or more but not more than 0,25 % and a total base number (TBN) of more than 20, # 45 % and more by weight and no more than 55 % by weight of mineral oil, # ###used in the manufacture of blends of additives for lubricating oils#
3811210028	#Additive consisting essentially of:### # Zinc bis(O,O-bis(2-ethylhexyl)) bis (dithiophosphate) (CAS RN 4259-15-8); # triphenyl phosphite (CAS RN 101-02-0) more than 0,5 % by weight but not more than 6 % by weight, # O,O,O-triphenyl phosphorothioate (CAS RN 597-82-0) more than 0,5 % by weight but not more than 6 % by weight, and not more than 7,5 % by weight of the combination of triphenylphosphorus compounds # 10 % or more by weight but not more than 20 % by weight of mineral oils, # ###used in the manufacture of blends of additives for lubricating oils#

3811210032	#Additive consisting essentially of:### # Zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis(phosphorodithioate) (CAS RN 2215-35-2), # 4 % or more by weight but not more than 12 % by weight of mineral oil, # ###used in the manufacture of blends of additives for lubricating oils#
3811900050	#Corrosion inhibitor containing :### # polyisobutenyl succinic acid and # more than 5 % and not more than 20 % by weight of mineral oils # ###for use in the manufacture of blends of additives for fuels#
3815909060	#Dinonylnaphthalenedisulfonic acid (CAS RN 60223-95-2) with a content by weight of 50 % or more but not more than 65 %, in the form of a solution in isobutanol (CAS RN 78-83-1)#
3815909089	#Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile#
3824999345	#Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5) containing by weight:### # not more than 20 % of disodium sulphate, and # not more than 10 % of sodium chloride #
3824999680	#Mixture consisting of:### # 64 % or more, but not more than 74 % by weight of amorphous silica (CAS RN 7631-86-9) # 25 % or more, but not more than 35 % by weight of butanone (CAS RN 78-93-3) and # not more than 1 % by weight of 3-(2,3-epoxypropoxy)propyltrimethoxysilane (CAS RN 2530-83-8) #
3902300095	#A-B-A block copolymer, consisting of:### # a copolymer of propylene and ethylene and # 21 % ( $\pm$ 3 %) by weight of polystyrene #
3902300097	#Liquid ethylene-propylene-copolymer with:### # a flashpoint of 250 °C or more, # a viscosity index of 150 or more, # of a number average molecular weight (M <sub>n</sub> ) of 650 or more #
3903909020	#Copolymer in the form of granules containing by weight:### # 83 $\pm$ 3 % styrene, # 7 $\pm$ 2 % n-butyl acrylate, # 9 $\pm$ 2 % n-butyl methacrylate and # 0,01 % or more but not more than 1 % of polyolefinic wax #
3903909060	#Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, in flake or powder form### #
3907299960	#Polytetramethylene oxide di-p-aminobenzoate#
3910000045	#Dimethyl siloxane, hydroxy-terminated polymer with a viscosity of 38-100 mPa·s (CAS RN 70131-67-8)#
3917310030	#Tubings:### # with an outer diameter of 0,33 mm or more but not more than 3,3 mm, # with an inner diameter of 0,01 mm or more but not more than 2,1 mm, # suitable for a maximum working pressure rate from 2,7 MPa up to 70 MPa, # suitable for all solutions used in chromatography, # whether or not with fused silica, # whether or not covered with PEEK, # ###for use in chromatographic system#
3917400020	#Plastic fittings (kit of nuts and ferrules or nuts) and connectors:### # threaded, # supported with or without a stainless steel ring, # suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, # ###for tubings with:### # outer diameter of 0,33 mm or more but not more than 3,3 mm, # suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, # suitable for all solutions used in chromatography, # ###for use in the production of chromatographic systems#

3919108075	#Self-adhesive reflecting film, consisting of several layers including:#### # a copolymer of acrylic resin, # polyurethane, # a metallised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use, # glass microspheres, and # an adhesive layer, with a release liner on one or both sides #
3920202150	#Biaxially oriented film of multiple layers of polypropylene, with a total thickness of not more than 14 micron#
3920610050	#Coextruded film of polycarbonate main layer and polymethyl methacrylate top layer with a:#### # total thickness of more than 230 µm but not more than 270 µm, # top layer thickness of more than 40 µm but not more than 55 µm, # defined surface roughness of the top layer of 0,5 µm or less (according to ISO 4287), # UV-stabilized top layer #
3920992850	#Thermoplastic polyurethane film (TPU) based on an aliphatic polycaprolactone (PCL), transparently backed on one side with a removable protective film (PET film), with a light transmission of more than 93 % (according to DIN EN ISO 13468-1), with a thickness of 25µm or more but not more than 500µm#
3920992870	#Sheets on rolls, consisting of epoxy resin, with conducting properties, containing:#### # microspheres with a coating of metal, whether or not alloyed with gold, # an adhesive layer, # with a protective layer of silicone or poly(ethylene terephthalate) on one side, # with a protective layer of poly(ethylene terephthalate) on the other side, and # with a width of 5 cm or more but not more than 100 cm # with a length of not more than 2 000 m #
3921190050	#Porous membrane of polytetrafluorethylene (PTFE) laminated to a polyester spunbonded non-woven cloth with#### # a total thickness of more than 0,05 mm but not more than 0,20 mm, # a water entry pressure between 5 and 200 kPa according to ISO 811, and # an air permeability of 0,08 cm <sup>3</sup> /cm <sup>2</sup> /s or more according to ISO 5636-5 #
3921905570	#Membrane composed of a polyamide layer and a polysulfone layer on a polyethylene terephthalate support layer with:#### # a total thickness of 0,25 mm or more but not more than 0,40 mm, # a total weight of 109 g/m <sup>2</sup> or more but not more than 114 g/m <sup>2</sup> #
3926909758	#Plastic ferrules and/or plugs:#### # supported with or without a stainless steel ring, # suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, # ####for tubings with:#### # outer diameter of 0,33 mm or more but not more than 3,3 mm, # suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, # suitable for all solutions used in chromatography, # ####for use in the production of chromatographic systems#
4009420020	#Rubber brake hose with:#### # textile strings, # a wall thickness of 3,2 mm, # a metal hollow terminal pressed on both ends, and # one or more mounting brackets, # ####for use in the manufacture of goods of Chapter 87#
4016995710	#Air intake hose for air supply to the combustion part of the engine comprising at least:#### # one flexible rubber hose, # one plastic hose, and # metal clips, # whether or not a resonator # ####for use in the manufacture of goods of Chapter 87#
5404190060	#Chemically tapered synthetic filaments of polyester with:#### # a diameter of 0,1 mm or more but not more than 0,6 mm, # a length of 30 mm or more but not more than 120 mm, # ####for use in the manufacture of paintbrushes#

5603929080	#Non-woven polyolefin fabric, consisting of an elastomeric layer, laminated on each side with polyolefin filaments:### # a weight of 25 g/m <sup>2</sup> or more but not more than 150 g/m <sup>2</sup> , # in the piece or simply cut into squares or rectangles, # not impregnated, # with cross-directional or machine-directional stretch properties # ###for use in the manufacture of infant/child care products#
5903209020	#Two layers' plastic-laminated textile fabric with:### # one layer consisting of knitted or crocheted polyester textile fabric, # other layer consisting of polyurethane foam, # a weight of 150 g/m <sup>2</sup> or more, but not more than 500 g/m <sup>2</sup> , # a thickness of 1 mm or more, but not more than 5 mm # ###for use in the manufacture of the retractable roof of motor vehicles#
5906999030	#Woven and coated rubberised textile fabric with the following characteristics:### # with three layers, # the outer layers consist of a natural rubber, EPDM and chloropen rubber compound, # the middle layer consists of polyester fabric, # ###for use in the manufacture of life rafts#
7007111010	#Specifically shaped and toughened safety glass:### # with a width of 200 mm or more but not more than 600 mm, # with a height of 150 mm or more but not more than 500 mm, # ###for use in the manufacture of motor vehicle window assemblies#
7019710050	#Non-woven product of non-textile glass fibre, for the manufacture of air filters or catalysts#
7020001010	#Television pedestal stands with or without bracket for fixation to and stabilization of television cabinet case/body#
7201101110	#Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm#
7609000030	#Aluminium connecting block for automotive air conditioning systems: ### # with a T6 hardening, # equipped with round stubs with a circumferential outer groove, # with through or non-through holes, made of profiles with an upper radius of 8 mm or more but not more than 11 mm, and a lower radius of 12 mm or more but not more than 17 mm, # with a distance between holes of 15 mm or more but not more than 22 mm, # with sockets designed for brazing or clamping, # with mounting holes for M6 or M8 mounting screw, threaded or not, # with a width of 5 mm or more but not more than 16 mm, # for connecting a compressor, a condenser, an evaporator, a chiller and other lines #
7616999070	#Connecting components for use in the production of helicopter tail rotor shafts#
8108903060	#Forged cylindrical bars of titanium with:### # a purity of 99,995 % by weight or more, # a diameter of 140 mm or more but not more than 200 mm, # a weight of 5 kg or more but not more than 300 kg # ### ##### #
8108903070	#Wire of an titanium alloy containing by weight:### # 22 % (± 1 %) of vanadium, and # 4 % (± 0,5 %) of aluminium # ###or### # 15 % (± 1 %) of vanadium, # 3 % (± 0,5 %) of chromium, # 3 % (± 0,5 % of tin and # 3 % (± 0,5 %) of aluminium #
8108909030	#Parts of spectacle frames and mountings, including### # temples, # blanks of a kind used for the manufacture of spectacle parts and # bolts of the kind used for spectacle frames and mountings, # ###of a titanium alloy#

8407341010	#Spark-ignition reciprocating or rotary internal combustion piston engines, with:### # a cylinder capacity of 1 200 cm <sup>3</sup> or more but not more than 2 000 cm <sup>3</sup> # a power of 95 kW but not more than 135 kW, # a weight of not more than 120 kg, # ###for use in the manufacture of motor vehicles of heading 8703#
8408906520	#Compression-ignition internal combustion piston engines:### # of the inline type, # with a cylinder capacity of 7 000 cm <sup>3</sup> or more but not more than 18 100 cm <sup>3</sup> , # with a power of 205 kW or more but not more than 597 kW, # with an exhaust after-treatment module, # with external width/height/depth dimensions of not more than 1 310/ 1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm, # ###for use in the manufacture of crushing, screening, separation or compost turning machines#
8409910040	#Fuel injector with solenoid valve for optimized atomization in the combustion chamber for use in the manufacture of spark-ignition internal combustion piston engines of motor vehicles#
8409990010	#Injectors with solenoid valve for optimised atomisation in the engine combustion chamber#
8413705120	#Electric brushless direct current motor with single-stage, radial flow pump centrifugal single entry impeller mounted on motor's shaft and volute with integrated heater of nominal power of 1800 W and soldered safety devices, monobloc with the motor, with:### # a discharge outlet diameter of 20 mm or more, # 9 slots stator, # 6 pole rotor, # rated power of 95 W, # volute with straight outlet, # rotor chamber without sand filter #
8413705130	#Electric brushless direct current motor with single-stage, radial flow pump centrifugal single entry impeller mounted on motor's shaft and volute with integrated heater of nominal power of 1800 W and soldered safety devices, monobloc with the motor, with:### # a discharge outlet diameter of 20 mm or more, # 9 slots stator, # 6 pole rotor, # rated power of 95 W, # volute with clamped rubber hose outlet, # rotor chamber without sand filter #
8414593530	#Electric blower for cooling the high-voltage battery of a hybrid passenger car with:### # a control unit, # MOSFET inverter, # a voltage of 9 V or more but not more than 16 V, # ambient temperature of – 40 °C or more, but not more than 80 °C, # ###for use in the manufacture of hybrid passenger cars#
8479907040	#Housing of the rotor part of the mechanical unit ensuring the adjustment of movement of the camshaft compared to the crankshaft:### # of a circular shape, # made of steel alloy with sintering process, # with not more than 8 oil chambers, # with a Rockwell hardness of 55 or more, # with a density of 6,5 g/cm <sup>3</sup> , or more, but not more than 6,7 g/cm <sup>3</sup> #
8481309130	#Mechanical check (non-return) valve for opening and closing of the flow of fuel:### # with an operating pressure of not more than 250 MPa, # with a flow rate of 45 cm <sup>3</sup> /minute or more, but not more than 55 cm <sup>3</sup> /minute, # with 4 input holes, each of them with a diameter of 1,2 mm or more, but not more than 1,6 mm, # made of steel #
8481805920	#Pressure regulating valve for incorporation into compressors of motor vehicle air condition units#

8483908920	#Sprocket for continuous variable valve timing to optimize the process of filling the cylinders of an internal combustion engine with:### # case, # rotor, # at least 4 screws, # spring, # of an external diameter of 80 mm or more but not exceeding 95 mm, # of a thickness of 25 mm or more but not more than 35 mm, # ###for use in the manufacture of engines of motor vehicles#
8484200010	#Mechanical shaft seal for incorporation into rotary compressors for use in the manufacture of motor vehicle air condition units#
8501109964	#DC motor to control angular position of the flap to adjust gas flow in the Air Throttle and EGR valve:### # with Ingress Protection (IP) standard of IP69, # with a rotor speed of not more than 6 500 rpm when not loaded, # with a rated voltage of 12,0 V ( $\pm 0,1$ ), # of a specified temperature range of $- 40$ °C or more but not more than $+ 165$ °C, # with or without a connecting pinion, # with or without an engine connector, # with or without a flange, # with a diameter of not more than 40 mm (not including the flange), # with an overall height of not more than 90 mm (from the base to the pinion) #
8501339030	#Electric drive for motor vehicles, with an output of not more than 315 kW: #with an AC or DC motor with or without transmission, #with or without power electronics#
8501402035	#Electric AC motor, single-phase, with:### # a rated power of 120 W or more but not more than 150 W, # an input power of 280 W or more but not more than 350 W, # an external diameter without bracket connector and pulley of 145 mm or more but not more than 160 mm, # a rated speed of 2 680 rpm or more but not more than 3 000 rpm, # a weight of 4,2 kg or more but not more than 4,6 kg, # pulleys, a spindle and a tachometer, # ###for use in the manufacture of home appliance products#
8501402045	#Electric AC motor, single-phase, with:### # a rated power of 275 W or more, but not more than 325 W, # an input power of 600 W or more but not more than 700 W, # an external diameter without bracket and connector of 150 mm or more but not more than 170 mm, # a rated speed of 15 000 rpm or more but not more than 20 000 rpm, # a weight of 4,2 kg or more, # a pulley and a tachometer, # ###for use in the manufacture of home appliance products#
8501402050	#Electric AC motor, single-phase, with:### # a rated power of 300 W or more but not more than 370 W, # an input power of 600 W or more but not more than 700 W, # an external diameter without bracket and connector of 150 mm or more but not more than 170 mm, # a rated speed of 15 000 rpm or more but not more than 19 000 rpm, # a weight of 4,8 kg or more, # a pulley, # ###for use in the manufacture of home appliance products#
8501402055	#Electric AC motor, single-phase, with:### # a rated power of 275 W or more, but not more than 325 W, # an input power of 600 W or more but not more than 700 W, # an external diameter without bracket and connector of 160 mm or more but not more than 180 mm, # a rated speed of 15 000 rpm or more but not more than 19 000 rpm, # a weight of not more than 4,4 kg, # a pulley, # ###for use in the manufacture of home appliance products#
8501402060	#Electric AC motor, single-phase, with:### # a rated power of 275 W or more but not more than 325 W, # an output power of 550 W or more but not more than 600 W, # an input power of 800 W or more but not more than 1 000 W, # an external diameter of more than 150 mm but not more than 170 mm without the bracket, # a rated speed of more than 16 000 rpm but not more than 18 000 rpm, # a weight of 3,4 kg or more but not more than 3,7 kg, # a pulley, # ###for use in the manufacture of home appliance products#

8501510040	#Electric AC motor, three-phase, with:### # a rated power of 280 W or more but not more than 320 W, # an output power of 480 W or more but not more than 540 W, # an input power of 800 W or more but not more than 900 W, # an external diameter of 150 mm or more but not more than 170 mm, # a rated speed of 15 000 rpm or more but not more than 20 000 rpm, # a weight of 6 kg or more but not more than 6,4 kg, # a pulley and a tachometer, # ###for use in the manufacture of home appliance products#
8501535040	#Permanent magnet traction AC motor, with:### # a continuous power of 110 kW or more but not more than 150 kW, # a liquid cooled system, # a total length of 460 mm or more but not more than 590 mm, # a total width of 450 mm or more but not more than 580 mm, # a total height of 490 mm or more but not more than 590 mm, # a weight of not more than 310 kg, # 4 mounting points #
8503009833	#Stator for brushless motor of electrical power steering with a roundness tolerance of 50 µm#
8536699086	#High-Definition Multimedia Interface (HDMI) type socket or plug, built into a plastic or metal housing, with 19 pins or 20 pins in 2 rows, for use in the manufacture of products falling within headings 8521 or 8528#
8536700010	#Optical socket, plug or connector, for use in the manufacture of goods falling within headings 8521 or 8528#
8537109145	#Main hybrid system controller, diagnosing and controlling the elements of the hybrid propulsion system, with:### # a programmable memory, # a microprocessor, # at least one composite connector, # a voltage of 24 V, # with a length of 350 mm or more but not more than 400 mm, # with a width of 200 mm or more but not more than 250 mm, # with a height of 80 mm or more but not more than 120 mm, # in a metal housing #
8538909960	#Front control panel, in the form of a plastic box, with light guides, rotary switches, pressure switches and buttons switches, or other type of switches, without any electrical component, of a kind used in the dashboard of motor vehicles of Chapter 87#
8543709015	#Laminated electrochromic film consisting of:### # two outer layers of polyester, # a middle layer of acrylic polymer and silicone, and # two electric connection terminals # ### ##### #
8543709033	#High-frequency amplifier comprising one or more integrated circuits and one or more discrete capacitor chips, whether or not with IPD (integrated passive devices) on a metal flange in a housing#
8544300085	#Extension two-core cable with two connectors, containing at least:### # a rubber grommet, # a metal attachment bracket, # ###of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87#
8548009048	#Optical unit, containing at least### # a laser diode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm # an optical lens # a "Recording Photodetector Integrated Circuit" (PDIC) # a focussing and tracking actuator # ### #
8708101010	#Plastic cover for filling the space between the fog lights and the bumper whether or not with a chrome strip for use in the manufacture of goods of Chapter 87#

9032890050	#Gas panel for regulating and controlling of the gas flow rate, working with plasma technology, comprising### # an electronic mass flow regulator, suitable for receiving and sending of analogue and digital signals # four pressure transducers, # two or more pressure valves, # electric interfaces and # several connectors for gas lines # suitable for in-situ plasma bonding processes or for multi frequency bond activating processes # ### #
------------	---